

Protect 800 | 990 NV800 | NV990



MODEL

NV800 | NV900 | NV990

Wall mountable, countertop with table stand or mounted on portable high tower, supplied with 2m power cord.

CONSTRUCTION + COLOUR

NV800

Precision-cut fabricated metal casing in a white anti-bacterial powder coat finish.

NV990

Precision-cut fabricated metal casing in a silver anti-bacterial powder coat finish.

SPECIFICATIONS

ELECTRICAL RATING

Single Phase, 220-240 VAC, 50-60 Hz
Fuse Rater at 250 VAC, 3 Amps, Listed

POWER CONSUMPTION

Maximum 14W

DIMENSIONS

366 mm (h) x 365 mm (w) x 114 mm (d)
14.4" (h) x 14.4" (w) x 4.5" (d)

WEIGHT

4.7kg | 104 lbs

ELECTRICAL CONNECTION

Switched and fused with a grounded, moulded power cord.

FAN AIR FLOW VOLUME

Speed I = 220 m³/hr | 129 CFM
Speed II = 260 m³/hr | 153 CFM

NOISE LEVEL

Speed I = 40 dB
Speed II = 45 dB

OPERATING CONDITIONS

10-35°C | 50-95°F, 10-75% Relative Humidity

SHIPPING/STORAGE CONDITIONS

5-50°C | 41-122°F, Maximum 95% Relative Humidity

QUALITY + SAFETY

Manufactured under ISO 9001, ISO 14001 & OHSAS 45001
IEC 60601-1, Third Edition
IEC 60601-1-2, Fourth Edition
IEC60335-1
Conforms to Low Voltage Directive (LVD)
2014/35/EU
CE Mark

